(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
8 November 2001 (08.11.2001)

PCT

(10) International Publication Number
WO 01/84883 A2

(51) International Patent Classification[7]: H04R 7/04

(21) International Application Number: PCT/US01/14199

(22) International Filing Date: 3 May 2001 (03.05.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/201,401 3 May 2000 (03.05.2000) US

(71) Applicant *(for all designated States except US)*: **WISDOM AUDIO CORP.** [US/US]; A Nevada Corporation, 3140 Research Way, Suite 72, Carson City, NV 89706 (US).

(72) Inventor; and

(75) Inventor/Applicant *(for US only)*: **BOHLENDER, Jack, T.** [US/US]; P.O. Box 294, Carson City, NV 89702 (US).

(74) Agent: **MARTIN, Rick**; Patent Law Offices of Rick Martin, PC, 416 Coffman Street, Longmont, CO 80501 (US).

(81) Designated States *(national)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States *(regional)*: ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: PLANAR SPEAKER WIRING LAYOUT



(57) Abstract: Trace runs for Planar Line Source Transducers (or speakers) are separated into multiple trace circuits which are electrically isolated but occupy the same area on the planar film. The separate trace runs are then driven with different electrical signals with tailored spectral content in order to achieve an overall acoustical frequency response. By having the separate trace runs occupy the same area, the line source nature of the transducer is preserved over the entire intended spectral response of the transducer and the mechanical structure is also kept simple. External spectral filtering circuits are used to pre-shape the spectral signal into each individual trace run and in most cases, the filtering components are passive and inexpensive.

Published:
— *without international search report and to be republished upon receipt of that report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

TITLE

Planar Speaker Wiring Layout

FIELD OF INVENTION

This invention relates to transducers which convert electrical energy into acoustical energy, one application being planar line source loudspeakers

BACKGROUND OF THE INVENTION

Planar transducers (also referred to as speakers) have a film composed of mylar, polyester, kapton, etc, suspended between rows of fixed magnetic bars composed of ceramic, neodymium(a rare earth), etc. Electronic signals carrying the sound to be generated are sent through the wires imbedded in the film. The variable magnetic fields created by the thin wires interact with the nearby fixed magnets to vibrate the film, thereby creating sound waves. They are similar to electrostatic speakers only in that thin film propagates the sound waves. Electrostatics don't use magnets, but create a magnetic field by reciprocating the field back and forth through high voltage stators via a transformer. A planar can handle much more power and produce higher sound pressure levels (SPL). The best version of a planar is a Line Source type. A "Line Source" version planar is narrow in width and very long compared to its width. This produces a cylindrical pattern, yielding enormous lateral coverage and almost no directionality above or below the ends of the driver. They also are very rugged and present an almost purely resistive load to the amplifier. Line source speakers can also handle a lot of

power as the relatively large area of film results in a large distribution of the power. Developed many years ago, they have recently become more popular with the advent of high power magnets, durable thin films, advanced adhesives to hold the aluminum traces to the film, sturdier metals for lighter framework, and tensioning techniques. No other speaker design offers the low distortion, excellent coverage, even dispersion, limited ceiling-floor reflections, and high SPL's as does a Planar Line Source.

Higher frequency audio components are more directional, and it has been discovered that in a diaphragm type transducer, it is desirable to have the higher frequency audio sounds emanate from a narrow and long strip like zone or area of the vibrating diaphragm. If the strip transducer is oriented in an upright position, the higher frequency audio sounds will emanate horizontally in substantially all directions resulting in a more uniform distribution of the audio signal. Sound attenuates only 3 dB for each doubling of distance instead of 6 dB as in conventional point source speakers. This provides for more consistent coverage and minimizes lost acoustic power.

Lower audible frequencies on the other hand do not tend to be as directional as the higher frequencies and can either be handled with a planar speaker or a separate more conventional point source speaker with no loss in performance.

US patent number 3,919,499 (incorporated herein by reference) (November 11, 1975) discloses a planar film speaker composed of planar zones where each zone may have

a separate circuit for reproducing a different spectrum of the audio signal.

US patent number 4,037,061 (incorporated herein by reference) (July 19, 1977) discloses a mechanical structure which permits a rapid and relatively simple assembly where the tolerances are automatically obtained as a result of the transducer design.

US patent number 3,919,499 (incorporated herein by reference) is believed to be the closest prior art. However, it differs from this invention in that the different line circuits for reproducing different audio spectrum are in separate structures or locations which can require a larger physical structure or result in a larger aperture which may diminish the speaker's "sweet spot" area of audio sound reproduction.

SUMMARY OF THE INVENTION

The main aspect of this invention is to create electrically separate line trace runs which occupy the same area on the vibrating film with the intention of driving the separate trace runs with different spectral components of the input signal. By having the separate line runs occupy the same area, the line source nature of the speaker is achieved with excellent frequency response.

One of the drawbacks of a planar line source speaker is that the higher frequencies above 10,000 to 20,000 Hz are somewhat rolled off (not as loud) in comparison to the lower frequencies. Also, there is typically some

amplitude peaking in the mid audio range. This peaking must be eliminated by a notch filter which attenuates the input signal in the frequency range of the peaking. One aspect of this invention is to improve the audio output frequency response in a simple and economical manner while preserving the line source characteristics of the transducer.

A line trace circuit is a single continuous conductor mechanically mounted to the vibrating film. In the prior art, multiple sets of line trace circuits have been used to reproduce different audio spectrums. The different circuits have been physically separated. In some cases, the structure of the speaker is different in the areas of the different line traces complicating the design and also resulting in different parts of the signal spectrum emanating from separate line acoustical radiation sources. For example, the spacing between the vibrating film and the magnet structure may be different in the two areas. Another aspect of this invention is to implement separate line trace circuits but to allow the circuits to be physically close so as to have similar audio spatial and dispersion outputs for the different frequency ranges.

It is also known that the larger the vibrating panel width, the smaller will be the audio sound dispersion angle. It is also an aspect of this invention to keep the width of the vibrating source as narrow as possible in order to better approximate a true line source with its improved dispersion angle.

Other aspects of this invention will appear from the following description and appended claims, reference

being made to the accompanying drawings forming a part of this specification wherein like reference characters designate corresponding parts in the several views.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a front plan view representation of a stereo speaker system.

Figure 2 is an end sectional view of a planar speaker taken along line 2-2 of figure 1.

Figure 3 is a prior art front plan view of the circuit run trace of a planar speaker.

Figure 4 is a front plan view of the trace runs of the preferred embodiment.

Figure 5 is the same as figure 4 with the addition of a frequency crossover circuit hookup.

Figure 6 is a circuit diagram including components for a passive crossover and lumped elements for the trace runs of the structure shown in figure 5.

DETAILED DESCRIPTION OF THE DRAWINGS

Referring to figure 1, a typical planar line source stereo speaker system is shown where **1** is the planar line source speaker and **2** is a conventional point source speaker used to enhance the low frequency response only.

In this figure, there are two sets L and R of transducers **1** and **2** in order to reproduce stereo audio. The length of the typical planar speaker **1** is typically from 40 inches to 75 inches tall and the sound aperture may only be on the order of 1 to 2 inches in order to best approximate a true acoustical line source. There is no limitation on the size or dimensions of the transducers.

Referring to figure 2, an end view of a typical planar speaker is shown. The magnet structure 3 is set up as sets of north/south magnet pairs 30 and 31, 32 and 33, 34 and 35 repelling each other from the top to the bottom magnet and also with alternating polarity in the dimension along the stretched film **5**. The framework **4** holds the magnets in place and also holds and stretches the film **5** on all four sides. The framework **4** can also hold the film **5** on only two sides in some applications. The magnets of magnet structure **3** are generally of a bar shape and can be composed of Ceramics, Neodymium (a rare earth) or other suitable magnetic materials.

Figure 3 is the planar film and structure for a prior art planar film speaker. **5** is the film which typically may be .3 millimeters thick and can be composed of Mylar, Polyester, Kapton or other materials. **6** is the electrical current carrying trace which is typically .3 millimeters thick and 3/16 inch wide and can vary in both thickness and width depending on the impedance desired. **7** is the positive connection terminal for the electrical current, and **8** is the negative connection terminal. The trace run specifically shown in the figure is referred to as a " six turn run" as the trace traverses the total length of the film six times in one continuous run. This prior art configuration has the drawback of producing

less acoustical energy in the higher frequency audible range.

Figure 4 is one embodiment of the invention in which there are two electrically separate trace runs essentially occupying the same area of the film. In this case, one continuous run transverses the length of the film four times ("four run") and the other only two times ("two run"). **13** is the four run trace and **14** is the two run trace. **9** is the positive terminal for the two run trace and **10** is the positive terminal for the two run trace. 11 is the negative terminal for the four run trace and **12** is the negative terminal for the two run trace. Other trace run configurations of either multiple independent circuits or different numbers of runs per trace can also be implemented depending on the desired results of impedance and frequency response.

Figure 5 is an embodiment of the invention including a frequency selective network **15**. **16** is the positive input from the power amplifier, and **17** is the negative input from the power amplifier. In figure 5, the current from the power amplifier is applied directly to the four run trace **13** but goes through the frequency selective network before going through the two run trace **14**. Therefore, the full frequency spectrum on the amplifier signal drives the four run circuit. The two run circuit **14,** however, is driven through a frequency selective network **15** which in one case only passes frequencies above where the four run trace circuit begins to naturally fall off or produce less acoustical energy. In one application, the frequency selective network is a passive (no external power is applied) high pass filter which allows only the spectral energy above 5,000 to

6,000 Hz to be applied to the two run circuit. The frequency shaping of the frequency selective network can of course vary on both frequency and filter characteristics in order to achieve the desired results of impedance and acoustical frequency response.

Figure 6 is an embodiment of the passive high frequency cross over network **15** along with a lumped element representation of the two and four line trace planar transducer. **19** is the lumped impedance of the four line trace **13** and **18** is the lumped impedance of the two line trace **14**. All component values can vary depending on the type of filter characteristics and impedance's desired, however, a typical value for the inductor **21** is 0.044 mHenry, and the typical value for the capacitor **20** value is 10 or 12 uFarad. The filter topology will change for other types of filters such as bandpass or lowpass.

In this embodiment, the frequency peaking at 5Khz to 6Khz of the single continuous prior art configuration is eliminated in the four run circuit **13** by having the extra frequency dependent impedance of the crossover circuit become significant in the region where the frequency peaking occurred. By driving the additional two run circuit **14** with only the higher frequencies, overall acoustic energy frequency flatness is achieved, and the audio energy exhibits the line source output with both a small aperture and constant radiation characteristics over the desired spectral energy range.

Although the present invention has been described with reference to preferred embodiments, numerous modifications and variations can be made and still the result will come within the scope of the invention. No

limitation with respect to the specific embodiments disclosed herein is intended or should be inferred.

I CLAIM:

1. A planar line source speaker comprising:
a magnet pair having a space between a first and a second member of the magnet pair;
a vibratable film mounted across the space;
a first line trace circuit mounted on the vibratable film; and
a second line trace circuit mounted adjacent to the first line trace circuit.

2. The apparatus of claim 1, wherein the first line trace circuit is a four run trace, and the second line trace circuit is a two run trace.

3. The apparatus of claim 2, wherein the first line trace circuit is rectangular, and the second line trace circuit is rectangular having a size to fit inside a boundary of the first line trace circuit.

4. The apparatus of claim 3, wherein the second line trace circuit further comprises a frequency selective network means functioning to only pass frequencies above where the first line trace circuit begins to naturally fall off.

5. The apparatus of claim 4, wherein the frequency selective network means further comprises a passive high pass filter which allows only a spectral energy above a range of about 5000 to 6000 Hz to be applied to the second line trace circuit.



Figure 1



Figure 2



Figure 3

(PRIOR ART)



Figure 4



Figure 5



Figure 6

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
8 November 2001 (08.11.2001)

PCT

(10) International Publication Number
WO 01/084883 A3

(51) International Patent Classification[7]: H04R 7/04, 9/00

(21) International Application Number: PCT/US01/14199

(22) International Filing Date: 3 May 2001 (03.05.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/201,401 3 May 2000 (03.05.2000) US

(71) Applicant *(for all designated States except US)*: **WISDOM AUDIO CORP.** [US/US]; A Nevada Corporation, 3140 Research Way, Suite 72, Carson City, NV 89706 (US).

(72) Inventor; and

(75) Inventor/Applicant *(for US only)*: **BOHLENDER, Jack, T.** [US/US]; P.O. Box 294, Carson City, NV 89702 (US).

(74) Agent: **MARTIN, Rick**; Patent Law Offices of Rick Martin, PC, 416 Coffman Street, Longmont, CO 80501 (US).

(81) Designated States *(national)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States *(regional)*: ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,

[Continued on next page]

(54) Title: PLANAR SPEAKER WIRING LAYOUT



(57) Abstract: Trace runs for Planar Line Source Transducers (or speakers) are separated into multiple trace circuits which are electrically isolated but occupy the same area on the planar film. The separate trace runs are then driven with different electrical signals with tailored spectral content in order to achieve an overall acoustical frequency response. By having the separate trace runs occupy the same area, the line source nature of the transducer is preserved over the entire intended spectral response of the transducer and the mechanical structure is also kept simple. External spectral filtering circuits are used to pre-shape the spectral signal into each individual trace run and in most cases, the filtering components are passive and inexpensive.

WO 01/084883 A3

IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:
— *with international search report*

(88) Date of publication of the international search report:
13 February 2003

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

INTERNATIONAL SEARCH REPORT

Int nal Application No
PCT/US 01/14199

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H04R7/04 H04R9/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 H04R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)
EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X Y	US 5 003 609 A (MURAOKA KAZUYUKI) 26 March 1991 (1991-03-26) column 3, line 15 -column 4, line 41; figures	1-3 4,5
Y	US 3 919 499 A (WINEY JAMES M) 11 November 1975 (1975-11-11) cited in the application column 1, line 14 -column 2, line 61; figures	4,5
X	US 5 297 214 A (BRUNEY PAUL F) 22 March 1994 (1994-03-22) column 5, line 6 -column 6, line 9; figures	1

-/--

[X] Further documents are listed in the continuation of box C.

[X] Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
9 October 2002	16/10/2002

Name and mailing address of the ISA	Authorized officer
European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Gastaldi, G

Form PCT/ISA/210 (second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 01/14199

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication,where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 996 311 A (SONIC WINDOW KABUSHIKI KAISHA) 26 April 2000 (2000-04-26) column 14, line 35 -column 17, line 1; figures	1
A	US 5 953 438 A (PORRAZZO EDWARD M ET AL) 14 September 1999 (1999-09-14) column 2, line 56 -column 4, line 31; figures	1
A	US 4 468 530 A (TORGESON W LEE) 28 August 1984 (1984-08-28) column 2, line 61 -column 3, line 20; figures	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

In nal Application No
PCT/US 01/14199

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 5003609	A	26-03-1991	JP	1208100 A	22-08-1989
			JP	1253399 A	09-10-1989
US 3919499	A	11-11-1975	DE	2500986 A1	24-07-1975
			JP	1037578 C	24-03-1981
			JP	50107919 A	25-08-1975
			JP	55028600 B	29-07-1980
US 5297214	A	22-03-1994	US	4939784 A	03-07-1990
			US	5148493 A	15-09-1992
EP 0996311	A	26-04-2000	BR	9815503 A	14-11-2000
			EP	0996311 A1	26-04-2000
			JP	3159714 B2	23-04-2001
			CN	1262857 T	09-08-2000
			WO	9903304 A1	21-01-1999
			RU	2179788 C2	20-02-2002
			TW	413994 B	01-12-2000
US 5953438	A	14-09-1999	US	5430805 A	04-07-1995
US 4468530	A	28-08-1984	EP	0099410 A1	01-02-1984
			WO	8302708 A1	04-08-1983